



TÜRK STANDARDLARI ENSTİTÜSÜ
TÜRK STANDARDLARINA UYGUNLUK BELGESİ
TURKISH STANDARDS INSTITUTION
CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS

Markanın Tanımı Description of the Mark
TSE veya/or  veya/or T S E

BELGE NUMARASI

REFERENCE NUMBER OF LICENCE

0202855-TSE-02/01

BELGENİN İLK VERİLİŞ TARİHİ

DATE OF FIRST ISSUE OF LICENCE

18.02.2019

BELGENİN SON GEÇERLİLİK TARİHİ

LICENCE VALID UNTIL

18.02.2020

BELGE SAHİBİ KURULUŞUN ADI

NAME OF THE LICENCE HOLDER

QATAR MINERAL FIBERS

BELGE SAHİBİ KURULUŞUN ADRESİ

ADDRESS OF THE LICENCE HOLDER

FACTORY 339, STREET 7, SECTOR 81 NEW INDUSTRIAL AREA
DOHA/QATAR Ad Dawhah/KATAR

ÜRETİM YERİ ADI

NAME OF THE MANUFACTURING PLACE

QATAR MINERAL FIBERS FACTORY 339, STREET 7, SECTOR 81
NEW INDUSTRIAL AREA DOHA/QATAR Ad Dawhah

ÜRETİM YERİ ADRESİ

ADDRESS OF THE MANUFACTURING PLACE

FACTORY 339, STREET 7, SECTOR 81 NEW INDUSTRIAL AREA
DOHA Ad Dawhah / KATAR

İPTAL EDİLEN BELGE NUMARASI (Varsa)

INDICATION OF SUPERSEDED LICENCE (if any)

TESCİLLİ TİCARİ MARKASI

REGISTERED TRADE MARK

QATAR MİNAREL FİBERS

İLGİLİ TÜRK STANDARDI

RELATED TURKISH STANDARD

TS EN 13162+A1 / Isı yalıtım mamulleri - Binalar için - Mineral yünü
(MW) fabrikasyon mamuller - Özellikler / 02.04.2015

BELGE KAPSAMI

SCOPE OF LICENCE

THERMAL INSULATION PRODUCTS FOR BUILDINGS - FACTORY MADE MINERAL WOOL (MW) PRODUCTS
1)

REACTION TO FIRE: A1

THERMAL CONDUCTIVITY (λ): 0,039 W/M.K

THICKNESS LEVEL: T3

DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE AND HUMIDITY: DS(70, 90)

COMPRESSIVE STRESS OR COMPRESSIVE STRENGTH: CS (10/Y) 0.5

COATING: UNCOATED BOARD

PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED

2)

REACTION TO FIRE: A1

THERMAL CONDUCTIVITY (λ): 0,040 W/M.K

e-imzalı/e-signed

18.02.2019

Belgelendirme Merkezi Başkanı Adına
HAZAL MİNE SARIASLAN SENYEN

DEPUTY DIRECTOR OF CONSTRUCTION MATERIALS
SECTOR

*Bu belge, belgelendirilen ürünün, üretim yerinin Enstitümüzün belirlediği şartları karşıladığını da gösterir.

*Bu belge hiç bir suretle tahrif edilemez, kısmen veya okunmasını zorlaştıracak şekilde çoğaltılamaz, kazıntı ve silinti yapılamaz.

*TSE YAPI MALZEMELERİ SEKTÖRÜ MÜDÜRLÜĞÜ * Adres: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA * Tel: 0312 416 63 79* Faks: 0312-416 66 17

TSE BELGELENDİRME MERKEZİ BAŞKANLIĞI Adres: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Tel: 0 312 416 64 81 / 416 64 27, Faks: 0 312 416 66 17
e-posta : bmb@tse.org.tr , web : www.tse.org.tr





TÜRK STANDARDLARI ENSTİTÜSÜ
TÜRK STANDARDLARINA UYGUNLUK BELGESİ
TURKISH STANDARDS INSTITUTION
CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS



BELGE KAPSAMI (0202855-TSE-02/01nolu belge devamı) : QATAR MINERAL FIBERS

İLGİLİ TÜRK STANDARDI(RELATED TURKISH STANDARD) TS EN 13162+A1 / Isı yalıtım mamulleri - Binalar için - Mineral yünlü (MW) fabrikasyon mamulleri - Özellikler / 02.04.2015

THICKNESS LEVEL: T3
DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE AND HUMIDITY: DS(70, 90)
COMPRESSIVE STRESS OR COMPRESSIVE STRENGTH: CS (10/Y) 0.5
COATING: UNCOATED BOARD
PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED
3)
REACTION TO FIRE: A1
THERMAL CONDUCTIVITY (λ): 0,039 W/M.K
THICKNESS LEVEL: T3
DIMENSIONAL STABILITY UNDER SPECIFIED TEMPERATURE AND HUMIDITY: DS(70, 90)
COMPRESSIVE STRESS OR COMPRESSIVE STRENGTH: CS (10/Y) 0.5
COATING: UNCOATED BOARD
PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED
4)
REACTION TO FIRE: A2, s1, d0
THERMAL CONDUCTIVITY (λ): 0,038 W/M.K
THICKNESS LEVEL: T1
COMPRESSIVE STRESS OR COMPRESSIVE STRENGTH: CS (10)05
COATING: ALUMINUM COATED BOARD
PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED
5
REACTION TO FIRE: C, s1, d0
THERMAL CONDUCTIVITY (λ): 0,037 W/M.K
THICKNESS LEVEL: T1
COATING: ALUMINUM COATED BLANKET
PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED
6)
REACTION TO FIRE: A2
THERMAL CONDUCTIVITY (λ): 0,037 W/M.K
THICKNESS LEVEL: T1
COATING: CAGE WIRE COATED GALVANISED BLANKET
PLACE OF USE: THESE PRODUCTS CANNOT BE USED IF COMPRESSIVE CREEP IS NEEDED

e-imzalı/e-signed

18.02.2019

Belgelendirme Merkezi Başkanı Adına
HAZAL MİNE SARIASLAN SENYEN

DEPUTY DIRECTOR OF CONSTRUCTION MATERIALS
SECTOR

*Bu belge, belgelendirilen ürünün, üretim yerinin Enstitümüzün belirlediği şartları karşıladığını da gösterir.

*Bu belge hiç bir suretle tahrif edilemez, kısmen veya okunmasını zorlaştıracak şekilde çoğaltılamaz, kızıntı ve silinti yapılamaz.

*TSE YAPI MALZEMELERİ SEKTÖRÜ MÜDÜRLÜĞÜ * Adres: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA * Tel: 0312 416 63 79* Faks: 0312-416 66 17

*TSE BELGELENDİRME MERKEZİ BAŞKANLIĞI; Adres: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Tel: 0 312 416 64 81 / 416 64 27, Faks: 0 312 416 66 17
e-posta : bmb@tse.org.tr , web : www.tse.org.tr

